

Gearboxes



Speed up Gearboxes

Various ratios and Torque outputs

Male PTO shaft or
Female PTO Quick release

Part Number	Speed up Ratio	Power Kw	Input Torque Nm	Max Input Speed rpm	Input Shaft	Output Torque Nm	Max Output Speed rpm	Output Spine	Pump Flange Group Size
60004-4	1 : 3	10	180	540	PTO Female Q. R.	55	1680	25 x 22	2
60001-4	1 : 3	10	180	540	Male PTO Spline	55	1680	25 x 22	2
60004-5	1 : 3.5	10	186	540	PTO Female Q. R.	58	1836	25 x 22	2
60001-5	1 : 3.5	10	186	540	Male PTO Spline	58	1836	25 x 22	2
60004-6	1 : 3.8	10	159	540	PTO Female Q. R.	42	2052	25 x 22	2
60001-6	1 : 3.8	10	159	540	Male PTO Spline	42	2052	25 x 22	2
70008-2	1 : 2	20	490	540	Male & Female QR, Through shaft	160	1620	35 x 31	2/3
71004-4	1 : 3	20	490	540	PTO Female Q. R.	160	1620	35 x 31	2/3
71001-4	1 : 3	20	490	540	Male PTO Spline	160	1620	35 x 31	2/3
71004-5	1 : 3.5	20	460	540	PTO Female Q. R.	130	1836	35 x 31	2/3
71001-5	1 : 3.5	20	460	540	Male PTO Spline	130	1836	35 x 31	2/3
71004-6	1 : 3.8	20	437	540	PTO Female Q. R.	115	2052	35 x 31	2/3
71001-6	1 : 3.8	20	437	540	Male PTO Spline	115	2052	35 x 31	2/3
80003-5	1 : 3	36	489	540	PTO Female Q. R.	163	1620	40 x 36	3.5
80001-5	1 : 3	36	489	540	PTO Female Q. R.	163	1620	40 x 36	3.5
92001-3/3	1 : 3.1	40	990	806	Male PTO Spline	320	2500	40 x 36	3

Spline Adaptors for Speed up Gearboxes to Pump shaft

Coupling Part Number	Pump Size	Spline
10005	Group 2 Standard	25 x 22
10026	Group 2 (4 mm Key Width)	25 x 22
10012	Group 2 Standard	35 x 31
10044	Group 2 (4 mm key width)	35 x 31
10014	Group 3 Standard	35 x 31
10017	Group 3.5 Standard	40 x 36
10052	Group 3.5 (6 mm Key Width)	40 x 36

