


Technical features	
Switching pressure range:	From 5 Bar to 300 Bar
Maximum pressure:	From 300 Bar to 400 Bar
Working temperature:	-25°C ÷ +85°C
Hydraulic connection:	¼" BSP-F
Body material:	30x30mm square in anodized aluminum
Through holes for mounting on panel:	2 x Ø5,25mm wheelbase 20mm
Weight:	0,15 Kg
Fixed hysteresis value:	- Piston execution ~ 15% of end of scale at 20°C
Switching accuracy:	± 2% of end of scale at 20°C
Mechanical life:	10 ⁶ cycles at 70 bar (1000 PSI) at 20°C
Tightening torque max:	50 Nm
Electric features	
Maximum load:	5 A at 250 Volt AC, 0.25 A at 125 Volt DC
Type of electric contact:	Exchange contacts (Common, NO and NC) – SPDT
Electric connection acc. to DIN 43650:	M3 (30x30mm) / M4 (30x30mm) – IP65
Electric connection acc. to IEC 60947-5-2:	M12 – IP67
Electric protection acc. to EN 60529:	M3, M4 – IP65 / M12 – IP67
ATEX certification:	ATEX II 3G Ex nc IIB T6 Gc IP65
Other	
Also available:	- Special value of hysteresis - CU-TR for Russian market - UL-CSA for electric part only
Warranty:	see dedicated page



Adjustment instructions



F5.	Switching Pressure range	Execution	P Max	Hydraulic Connection	Type of Seal	Electric contacts	Setting pressure	Condition	Type of execution	Type of Electric Connection
Type	Bar						Bar			
F53	5>50	Piston	300	¼" BSP-F	V VITON	G Gold plated contacts (if omitted means silver plated contacts)	If requested, Indicate the value setting pressure, also indicate the condition "D" or "U"	D Means falling pressure setting, also please indicate the value	P Execution with adjustable graduate knob	M12 connector 12x1
F55	15>150	Piston	350		E EPDM					
F57	30>300	Piston	400		If omitted means NBR					